

SAFETY DATA SHEET

Illumitex Waterbased Lacquer

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

PRODUCT NAME: Illumitex Waterbased Lacquer
SYNONYMS, TRADE NAMES: DA08 + 000, 998
APPLICATIONS: Application by brush or roller. For professional use only.
SUPPLIER: Pittaway Special Coatings Ltd, 106-114 Flinton Street, Hull, HU3 4NA
EMERGENCY TELEPHONES: 01482 329007

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	CONTENTS	HEALTH (class)	RISK (R No.)
PROPAN-2-OL	67-63-0	2.5-10%	-	

COMPOSITION COMMENTS : Substances presenting a hazard within the meaning of the Chemicals (Hazard information and Packaging) Regulations 1993 and subsequent amendments (Directives 67/584/EEC 88/379/EEC).

3. HAZARDS IDENTIFICATION

4. FIRST AID MEASURES

GENERAL: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
EYES: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.
INHALATION: Remove to fresh air and keep warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
INGESTION: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use sand, alcohol resistant foam, carbon dioxide, chemical powder, water fog for larger fires. Do not use water jet.
SPECIAL FIRE FIGHTING PROCEDURES: As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS: Exclude non essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials e.g. sand and place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid the use of solvents. If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of rivers, streams or lakes, the National Rivers Authority.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Prevent, or if not reasonably practicable, control personal exposure to within the relevant occupational exposure limits. Keep the container tightly closed. Exclude sources of ignition. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Never use pressure to empty; the container is not a pressure vessel. Always keep in containers of the same material as the supply container. Good housekeeping standards and regular safe removal of waste materials will minimise the risk of spontaneous combustion and other fire hazards.

STORAGE PRECAUTIONS: Store separately from oxidising agents and strongly acidic or strongly alkaline materials. Observe the label precautions. Store between 5 and 35C in dry, well ventilated places away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. The principles contained in the HSE guidance note "Storage of Packaged Dangerous Substances" should be observed when storing this product.

ILUMITEX WATERBASED LACQUER

15. REGULATORY INFORMATION

SAFETY PHRASES:	S-23	Do not breathe gas/fumes/vapour/spray.
	S-24	Avoid contact with skin.
	S-37	Wear suitable gloves.
	S-51	Use only in well ventilated areas.

UK REGULATORY

REFERENCES:

This product is classified and labelled for supply in accordance with the Chemicals (hazard information and packaging for supply) Regulations 1994 and subsequent amendments (Directive 88/379/EEC). The safety data sheet does not constitute the users own assessment of the workplace risk as required by other Health and legislation e.g. the Control of Substances Hazardous to Health Regulations 1988.

Safety

16. OTHER INFORMATION

Revision Date: 1-10-97

PITTAWAY SPECIAL COATINGS LTD, 106-114 FLINTON STREET, HULL, HU3 4NA - TEL 01482 329007