

SAFETY DATA SHEET

ILUMITEX PRIMER SEALER

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: Ilumitex Primer Sealer
COMPANY: Pittaway Special Coatings Ltd, 106-114 Flinton Street, Hull, HU3 4NA
TELEPHONE: 01482 329007
FAX: 01482 213053

2. INTENDED USE

Sealer for the Ilumitex and Ilumitextra systems.

Application is by brush or roller.
Application instruction included in pack.
Suitability for other uses should be referred to the manufacturer.

3. COMPOSITION

Vinyl acetate copolymer emulsion containing titanium dioxide, inert mineral extenders, water with additives to preserve and stabilise the product.

4. HAZARDS IDENTIFICATION

Water based emulsion paints have a low toxicity hazard; they do not present any undue hazard when handled with care, and as long as good standards of industrial and personal hygiene are observed. As with any paint product, persons known to have a history of dermatitis, skin sensitisation or asthma should not work in direct contact with water based paints except with medical approval.

Adequate general washing facilities and emergency eye wash equipment should be provided.

- a) Over exposures are irritating to the eyes and splashes entering the eye will cause discomfort and possible damage.
- b) Prolonged contact with the skin may have a de-fatting effect which may lead to skin irritation and in some cases dermatitis.

5. PRECAUTIONS IN HANDLING & USE

Avoid contact with skin and eyes. Wear appropriate clothing and eye protection to BS 2092. Barrier creams may help to protect exposed areas of skin but are not a substitute for full physical protection.

Keep containers closed except when in use.

6. FIRST AID PROCEDURE

Inhalation: Remove to fresh air, keep patient warm and at rest.
Eye Contact: Irrigate copiously with clean, fresh water for at least ten minutes, holding the eyelids apart.
Skin Contact: Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleaner. Do not use solvents or thinners.
Ingestion: There is no hazard by this route in normal industrial activities. If accidentally swallowed DO NOT INDUCE VOMITING, keep at rest and obtain medical attention.

In all cases of doubt, or where symptoms persist, seek medical attention.

7. STORAGE

Store in a cool, dry, well ventilated place. Keep out of reach of children. PROTECT FROM FROST.

8. FIRE PREVENTION

Since emulsion paints are water based, flammability is not a hazard; the small amounts of volatile organic substances present are not known to have caused fire or explosion.

9. FIRE FIGHTING

No special fire fighting requirements are necessary.

10. SPILLAGE

Small quantities of spilled emulsion paint can be washed away before it dries; larger amounts should be contained and collected on absorbent materials e.g. sand and earth. Do not allow to enter drains.

11. ENVIRONMENTAL

Waste materials must be disposed of in accordance with the general requirements of the Control of Pollution Act 1974.

12. ADDITIONAL INFORMATION

Protection of Eyes Regulations 1974, S.I. 1974 No.1681.